

AD-A151 470

UNIQUENESS AND STABILITY IN NONLINEAR ELASTICITY AND
VISCOELASTICITY(U) CARNEGIE-MELLON UNIV PITTSBURGH PA
DEPT OF MATHEMATICS M E GURTIN 14 JAN 85
ARO-18463. 13-NA DRAG29-82-K-0002

1/1

UNCLASSIFIED

F/G 12/1


NL



END

FORM

ONE



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS 1963 A

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

MASTER COPY - FOR REPRODUCTION PURPOSES

②

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ARO 18463.13-MA	2. GOVT ACCESSION NO. N/A	3. RECIPIENT'S CATALOG NUMBER N/A
4. TITLE (and Subtitle) Uniqueness and stability in nonlinear elasticity and viscoelasticity		5. TYPE OF REPORT & PERIOD COVERED 19 Oct 81 - 18 Oct 84 Final
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Morton E. Gurtin		8. CONTRACT OR GRANT NUMBER(s) DAAG29-82-K-0002
9. PERFORMING ORGANIZATION NAME AND ADDRESS Department of Mathematics Carnegie-Mellon University Pittsburgh, PA 15213		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS U. S. Army Research Office Post Office Box 12211 Research Triangle Park, NC 27709		12. REPORT DATE January 14, 1985
		13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) NA		
18. SUPPLEMENTARY NOTES The view, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) elasticity, phase transitions, viscoelasticity, viscoplasticity, plasticity, degenerate parabolic equations, free boundaries		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report contains a summary of research concerning finite elasticity, phase transitions, viscoelasticity, viscoplasticity, plasticity, degenerate parabolic equations, and free boundaries.		

DTIC
ELECTE
MAR 19 1985
E

AD-A151 470

DTIC FILE COPY

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

85

03

07

038

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

ARO 18463.13-MA

Uniqueness and Stability in
Nonlinear Elasticity and Viscoelasticity

Final Report

Morton E. Gurtin

January 14, 1985

U. S. Army Research Office

DAAG29-82-K-0002

Department of Mathematics
Carnegie-Mellon University
Pittsburgh, PA 15213

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



Finite elasticity.

Motivated by papers of Ball [R1], Ericksen [R2,R3], James [R4], Knowles [R5], Knowles and Sternberg [R6], and Gurtin and Temam [R7], we have developed a general theory for two-phase deformations of elastic solids [P1]. Our main results concern the stability of such deformations. We proved that if a two-phase deformation is a local minimizer, then given any point p_0 of the surface of discontinuity, the piecewise-homogeneous deformation corresponding to the two values $F^\pm(p_0)$ of the deformation gradient $F(p_0)$ is a global minimizer. We showed further that the Eshelby conservation law, which is a direct consequence of the equilibrium equations for smooth deformations, is not generally valid for two-phase deformations; it is a necessary and sufficient condition that the Maxwell relation be satisfied, and is therefore a necessary condition for the stability of the deformation.

A theory of structured phase transformations, based on an elastic stored energy which depends on strain gradients (in addition to strain) is being developed in collaboration with Marshall Slemrod (RPI) and Jack Carr (Heriot-Watt University, Scotland). We have recently completed an analysis of the one-dimensional problem - for a filament of finite length - subjected to end forces or prescribed end displacements. Among our results we showed that for the force problem the only stable solutions

are those with constant strain (two phase solutions are unstable), while for the displacement problem, there are stable two phase solutions, but such solutions contain, at most, a single transition [P2,P3]. (See also the survey papers [P4,P5].) We also determined the properties of such solutions; the resulting analysis is quite difficult, involving a singular perturbation near a homoclinic orbit.

Viscoelasticity. Viscoplasticity.

In collaboration [P6] with L. F. Murphy (Oregon State University) we have considered the problem of minimizing the thermal stress induced during the cooling or heating of a thermorheologically simple¹ viscoelastic body. (Problems of this type occur, for example, during the curing of polymers.) We show - under certain simplifying assumptions - that optimal paths for such problems are canonical: they are independent of the shape of the body.

In a joint work [P7] with R. V. Browning (Los Alamos National Laboratory) we have presented a simplified constitutive equation² which describes the one-dimensional response of certain filled polymers. This constitutive equation isolates the rate-dependent portion of the stress response in the form of a convolution of a single stress-relaxation function with a more-or-less standard elastic-plastic stress-strain law.

¹Cf., e.g., Muki and Sternberg [R8].

²This model is now being used - for the solution of actual problems - by the Los Alamos National Laboratory. Also, Lawrence Livermore Laboratory has developed (and coded) a three-dimensional theory [R9] based on our model.

To be precise, we introduced a "pseudo-stress" π which is related to the strain ϵ by a (rate-independent) elastic-plastic relation of the form

$$\pi = F(\epsilon, \epsilon_m),$$

where ϵ_m denotes the past maximum of strain. Then the stress σ is given by

$$\sigma(t) = \int_0^t G(t-s) \dot{\pi}(s) ds,$$

where G is a stress-relaxation function. The model has the virtue of simplicity, in that it models materials for which rate dependent behavior may be determined by a single stress relaxation test. The one-dimensional elastic-plastic function F is likewise easy to determine. We developed a straightforward process to determine these for three such polymers and found excellent fit to experimental data.

We have continued our work on stability in viscoelasticity; in particular, we have studied the buckling of a viscoelastic rod subject to suddenly applied arbitrarily-large axial end thrusts [P8]. In the literature one often sees the assertion that such problems have no solution. We show that this is true provided the loads are constant in time, but it is not true for certain time-dependent loadings. In particular, we show that:

- (i) if the load starts at the instantaneous buckling load and initially decreases less rapidly than the normalized relaxation function, the rod will buckle;
- (ii) if the load initially decreases more rapidly than the normalized relaxation function, the rod will not buckle.

The instantaneous buckling load is the buckling load calculated using the initial-value of the relaxation function. The above results demonstrate that the relaxation of a viscoelastic rod must be exploited in order to obtain buckled solutions.

Plasticity

We have developed [P9] a formulation of plasticity theory which utilizes a pair of hypoelastic stress-strain laws and a switching rule based on whether or not the current stress magnitude, $s(t)$, coincides with its past maximum

$$s_m(t) = \max_{\tau \leq t} s(\tau).$$

We do not find it necessary to introduce (a-priori) the notions of elastic and plastic strain or that of a yield surface.

We prove that our formulation is, modulo certain assumptions, completely equivalent to classical plasticity with the von Mises yield condition and isotropic work-hardening: the existence of the yield surface and the use of plastic work as hardening parameter are consequences of the theory rather than initial assumptions.

Finally, the concepts underlying our formulation - namely, stress-rate, strain-rate, and the past maximum of stress - possibly make this formulation amenable to the numerical solution of boundary-value problems.

Degenerate parabolic equations and free boundaries.

In collaboration with R. C. MacCamy and E. A. Socolovsky (Carnegie-Mellon University) we have studied degenerate diffusion problems in which free boundaries occur, our major objective being the development of numerical procedures which effectively track these boundaries. In [P10] we introduced our ideas in terms of the one-dimensional porous media problem (cf., e.g., Aronson [R10], Caffarelli and Friedman [R11], Friedman [R12], Peletier [R13]), with initial data supported in a finite interval $[\alpha, \beta]$, an assumption which gives rise to a free boundary. We exploit the fact that particles move along trajectories determined by the flow velocity and, most importantly, that the free surface is itself such a trajectory. Writing $X(p, t)$ for the position at time t of the particle which at $t = 0$ occupied p , the porous medium problem is formally equivalent to an initial-value problem¹ for X on a fixed interval $\alpha \leq x \leq \beta$. Moreover, and most important, the curves

¹Cf., Berryman [R14], whose work predates ours. Berryman also introduces Lagrangian coordinates (rather than the initial coordinate, Berryman takes $p = p(x, t)$ to be the total mass at t in the interval $(-\infty, x)$). Berryman's partial differential equation for X is simpler than ours, but his initial condition is more complicated.

$$x = X(\alpha, t), \quad x = X(\beta, t)$$

form the free boundary.¹

Our method of solving the porous medium problem is to solve the problem for X on the fixed interval $[a, \beta]$. The price paid for this conceptual simplicity is that the equation for X is highly nonlinear, but this does not appear to be a serious concern in the numerical solution. Preliminary numerical studies, based on a simple difference scheme, seem to indicate that, even with a fairly crude mesh, the free boundary is tracked quite accurately; in fact, the accuracy seems to be $O(h^2)$, at least for concave initial data.

General continuum mechanics.

Experimentalists often report strain-data using logarithmic measures of strain, and these measures have been utilized extensively in the recent engineering literature. Whenever the principal axes of strain are fixed throughout the motion, it is known that the simple relationship

$$\underline{D} = (\ln \underline{V})'$$

holds, with \underline{D} the stretching tensor and \underline{V} the left stretch tensor. Previous work, however, failed to find an analogous formula in the general case. Some researchers have therefore

¹This affords a method of studying the regularity of the free-boundary, a method subsequently used for that purpose by Höllig and Pilant [R15].

concluded that the strain measure $\ln \underline{V}$ has very limited applicability. In [P11], written in collaboration with K. Spear (Georgia Tech), we established the precise circumstances in which the above formula holds. We also found a simple relationship between \underline{D} and the time derivative of $\ln \underline{V}$ measured by an observer rotating with the axes of \underline{V} and showed that, for sufficiently small deformations, the Jaumann time-derivative of $\ln \underline{V}$ is a good approximation to \underline{D} .

Miscellaneous.

A paper [P12] was written discussing problems in continuum mechanics and population dynamics which are as yet unsolved, and which seem of interest from both mathematical and physical points of view. The first problem concerns the buckling of a viscoelastic, Euler-Bernoulli beam (cf. [P8]). The resulting system of equations forms a nonlinear eigenvalue problem with the buckled state dependent on the loading history. Based on our formulation, Puel and Mignot [R16] have developed a fairly complete solution.

The second problem is that of minimizing the residual stress that occurs during the cooling of a constrained viscoelastic material. What makes the problem interesting is the lack of convexity of the underlying cost function.

The third problem deals with the dispersal of age-dependent biological populations. Under certain simplifying assumptions the general system reduces to a pair of reaction-diffusion equations which are in some ways degenerate-parabolic. Existence for the

corresponding initial-value problem with compactly supported data has since been established by Hernandez [R17] in his thesis written under D. Aronson (University of Minnesota).

Participating Scientific Personnel

Kathleen Spear (who earned a Ph.D. degree while employed on the project.

References

Papers which appeared under this contract (1981-1984)

- P1 Gurtin, M. E., Two phase deformations of elastic solids. Archive for Rational Mechanics and Analysis, 84, 1-29 (1983).
- P2 Gurtin, M. E., J. Carr, and M. Slemrod, One-dimensional structured phase transformations under prescribed loads, Journal of Elasticity. Forthcoming.
- P3 Gurtin, M. E., J. Carr, and M. Slemrod, Structured phase transitions on a finite interval, Archive Rational Mechanics and Analysis, 84, 317-351 (1984).
- P4 Gurtin, M. E., One-dimensional structured phase transitions on finite interval, Proceedings, 5th Symposium of the International Society for the Interaction of Mechanics and Mathematics. Forthcoming.
- P5 Gurtin, M. E., On phase transitions with interfacial energy, Proceedings, Conference on Phase Transformations and Material Instabilities in Solids, Mathematics Research Center, University of Wisconsin. Forthcoming.
- P6 Gurtin, M. E. and L. Murphy, Optimal temperature paths for thermorheologically simple viscoelastic materials with constant Poisson's ratio are canonical, Quarterly of Applied Mathematics. Forthcoming.
- P7 Browning, R. V., Gurtin, M. E., and W. O. Williams, A viscoplastic constitutive theory for filled polymers. International Journal of Solids and Structures. Forthcoming.
- P8 Gurtin, M. E., V. J. Mizel, and D. W. Reynolds, On nontrivial solutions for a compressed linear viscoelastic rod. Journal of Applied Mechanics, 49, 245-246 (1982).
- P9 Gurtin, M. E., On the hyperelastic formulation of plasticity using the past maximum of stress. Journal of Applied Mechanics. 50, 894-896 (1983).
- P10 Gurtin, M. E., R. C. MacCamy, and E. A. Socolovsky, A coordinate transformation for the porous media equation that renders the free boundary stationary, Quarterly of Applied Mathematics. Forthcoming.
- P11 Gurtin, M. E. and K. Spear, On the relationship between the logarithmic strain rate and the stretching tensor. International Journal of Solids and Structures, 19, 437-444 (1983).
- P12 Gurtin, M. E., Some questions and open problems in continuum mechanics and population dynamics. Journal of Differential Equations, 48, 293-312 (1983),

General References

- 1 Ball, J. M., Convexity condition and existence theorems in non-linear elasticity, Arch Rational Mech. Anal. 63, 337-403.
- 2 Ericksen, J. L., Equilibrium of bars, J. Elasticity 5, 191-201 (1975).
- 3 Ericksen, J. L., Continuous martensitic transitions in thermo-elastic solids, J. Thermal Stresses 4, 107-119 (1981).
- 4 James, R., Finite deformation by mechanical twinning, Arch. Rational Mech. Anal. 77, 143-176 (1981).
- 5 Knowles, J. K., The finite anti-plane shear field near the tip of a crack for a class of incompressible elastic solids, Int. J. Fracture 13, 611-639 (1977).
- 6 Knowles, J. K., and E. Sternberg, On the failure of ellipticity and the emergence of discontinuous deformation gradients in plane finite elastostatics, J. Elasticity 8, 329-379 (1978).
- 7 Gurtin, M. E., and R. Temam, On the anti-plane shear problem in finite elasticity, J. Elasticity 11, 197-206 (1981).
- 8 Muki, R., and E. Sternberg, On transient thermal stresses in viscoelastic materials with temperature-dependent properties, J. Appl. Mech. ASME 83, 193-207 (1961).
- 9 Simo, J. C. and R. L. Taylor, A simple 3-dimensional viscoelastic model accounting for damage effects. Rept. No. UCB/SESM-83/10, Dept. Civil Eng., U. California, Berkeley (1983).
- 0 Aronson, D. G., Regularity properties of flows through porous media, SIAM J. Appl. Math. 17, 461-468 (1969).
- 1 Caffarelli, L. A., and A. Friedman, Regularity of the free boundary of a gas flow in an n-dimensional porous medium, Indiana Univ. Math. J. 29, 361-391 (1980).
- 2 Friedman, A., Variational Principles and Free-Boundary Problems, Wiley (1982).
- 3 Peletier, L. A., The porous media equation, in Application of Nonlinear Analysis in the Physical Sciences (eds. H. Amann, N. Bazley, K. Karchgassner) Pitman, 229-241 (1981).

- R14 Berryman, J. G., Evolution of a stable profile for a class of nonlinear diffusion equations, III. slow diffusion on the line, J. Math. Phys. 21, 1326-1331 (1980).
- R15 Höllig, K. and M. Pilant, Regularity of the free boundary for the one dimensional porous medium equation. Forthcoming.
- R16 Mignot, F. and J. P. Puel, Buckling of a viscoelastic rod. Arch. Rational Mech. Anal. Forthcoming.
- R17 Hernandez, G. E., Existence of solutions of population dynamics problems with diffusion. Ph.D. Thesis, Dept. Math. U. Minnesota (1983).

CARNEGIE-MELLON UNIVERSITY
5000 Forbes Avenue
Pittsburgh, PA 15213

FINAL
REPORT OF INVENTIONS

Contract/Grant Number: DAAG29-82-K-0002

Date of Contract/Grant: October 19, 1981

Period Covered: October 19, 1981 - October 18, 1984

I hereby certify that, to the best of my knowledge and belief, no inventions, improvements or discoveries, which reasonably appear to be patentable, were conceived or first actually reduced to practice by persons engaged in the performance of the work under the above contract/grant during the period indicated, except as follows:

Name of Inventor:

Title of Invention

By 

Title Professor of Mathematics

Date January 15, 1985

END

FILMED

4-85

DTIC